

Drop-in Cooker (with Metal Casing)

BKT18



Specification

Electricity	BKT179	220V, 60Hz, 1PH	Power Consumption	BKT179	1800 W
	BKT179(AG)			BKT179(AG)	
	BKT18-A			BKT18-A	
	BKT18-E			BKT18-E	
	BKT18-J			BKT18-J	
Power Connection	Plug type	Max Current	8.5 A		
Warming	1 ~ 2 (2 steps)	Heating	3 ~ 8 (6 steps)		
Conversion to Calory	1555.2 Kcal/h				
Temperature per Warming Steps	1	2	(1L Water, using chafer)		
	35 °C	60 °C			
Dimension / Weight	Product: 296 X 370 X 80 (mm) / 4kg Package: 490 X 360 X 170 (mm) / 7.1kg				
Controller Type	Touch screen (integrated into top glass)				
Cookware Diameter	min : Ø130mm max : Ø240mm	Loadable Weight	30 Kg		
Recommendation	Hotpot, Shabu shabu, Built-in on dining table				
Functions & Features	<input checked="" type="checkbox"/> Metal body makes the unit more durable				
	<input checked="" type="checkbox"/> Safety				
	- No vessel : "U" flashing				
	- Over current indication : "1" flashing				
	- Over voltage indication : "2" (Above 265V) flashing				
	- Low voltage : "3" (Below 180V) flashing				
	- Over heated product indication : "4" (IGBT heat sink temperature above 85°C) flashing				
	- Top surface overheated (empty vessel) : "6" (Top surface temperature above 260°C) flashing				
	- Unstable power indication: "7" flashing				
- Defective PCB indication : "8" flashing					
- Defective Working Coil indication : "9" flashing					
Warranty	1 year (to be charged in case of user's negligence)				

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.

Dimension (mm)	
Product	Installation Guide
Case Cut (using installation guide)	Case Cut (not using installation guide)
Table Cut (using installation guide)	Table Cut (for "L" type hole)
<p>Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>DIPO INDUCTION CO., Ltd. / www.dipole.com</p> <p>COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.</p>	

Drop-in Cooker (with Metal Casing)

BKT26



Specification

Electricity	BKT22	220V, 60Hz, 1PH	Power Consumption	BKT22	2600 W
	BKT22(AG)			BKT22(AG)	
	BKT26-A			BKT26-A	
	BKT26-E			BKT26-E	
	BKT26-CE1			BKT26-CE1	
	BKT24-J	200V, 50/60Hz, 1PH		BKT24-J	2400 W
Power Connection		Plug type	Max Current		12 A
Warming		1 ~ 2 (2 steps)	Heating		3 ~ 9 (7 steps)
Conversion to Calory		2246.4 Kcal/h			
Temperature per Warming Steps		1 35 °C	2 60 °C	(1L Water, using chafer)	
Dimension / Weight		Product: 296 X 370 X 80 (mm) / 4kg Package: 490 X 360 X 170 (mm) / 7.1kg			
Controller Type		Touch screen (integrated into top glass)			
Cookware Diameter		min : Ø130mm max : Ø240mm	Loadable Weight		30 Kg
Recommendation		Hotpot, Shabu shabu, Built-in on dining table			
Functions & Features		<input checked="" type="checkbox"/> Metal body makes the unit more durable <input checked="" type="checkbox"/> Safety - No vessel : "U" flashing - Over current indication : "1" flashing - Over voltage indication : "2" (Above 265V) flashing - Low voltage : "3" (Below 180V) flashing - Over heated product indication : "4" (IGBT heat sink temperature above 85°C) flashing - Top surface overheated (empty vessel) : "6" (Top surface temperature above 260°C) flashing - Unstable power indication: "7" flashing - Defective PCB indication : "8" flashing - Defective Working Coil indication : "9" flashing			
Warranty		1 year (to be charged in case of user's negligence)			

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.

Dimension (mm)	
Product	Installation Guide
Case Cut (using installation guide)	Case Cut (not using installation guide)
Table Cut (using installation guide)	Table Cut (for "L" type hole)
<p>Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>DIPO INDUCTION CO., Ltd. / www.dipole.com</p> <p>COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.</p>	