

Drop-in Cooker (with Plastic Casing)

BKPC



Specification

Electricity	220V, 60Hz, 1PH	Power Consumption	1000 W
Power Connection	Plug type	Max Current	4.5 A
Warming	C1 (1 warming step)	Heating	P1 ~ P6 (6 steps)
Conversion to Calory	864 Kcal/h		
Dimension / Weight	Ø245 X 60 (mm) / 1.5kg		
Controller	Capactive button (separated from the unit)		
Power Cable	900 mm		
Cookware Diameter	min : Ø85mm max : Ø165mm	Loadable Weight	20 Kg
Recommendation	1 person serving hotpot, shabu shabu and soup, Built-in on dining table		
Functions & Features	■ Safety		
	- No vessel : "0" flashing		
	- Low voltage indication : "1" flashing		
	- Over voltage indication : "2" flashing		
	- Low voltage : "3" flashing		
	- Broken or disconnected IGBT sensor : "4" flashing		
	- Top glass overheated (empty vessel) : "5" flashing		
- IGBT(main components) overheated : "6" flashing			
- Defective circuit : "7" flashing			
■ Timer Setting			
- Between 0-99min (set per a minute)			
Certification	Korean KC Certification		
Warranty	1 year (to be charged in case of user's negligence)		

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.

Dimension (mm)	
Product	Installation Guide
Case Cut (using installation guide)	Case Cut (not using installation guide)
Table Cut (using installation guide)	Table Cut (for "L" type hole)
Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412 R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412 DIPO INDUCTION CO., Ltd. / www.dipoele.com	
COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.	