





DIHR113RS




Specification

Electricity	DIHR3F2	380V 60Hz, 3PH+N	Power Consumption	DIHR3F2	10500 W			
	DIHR3F2-A	340-420V, 50/60Hz, 3PH+N		DIHR3F2-A				
	DIHR3F2-E			DIHR3F2-E				
	DIHR3F2-CE1			DIHR3F2-CE1				
DIHR3F2-J	DIHR3F2-J		9000 W					
Power Connection		Direct Conection to Circuit Breaker	Max Current		15 A			
Output to Calory		9072 Kcal/h						
Dimension / Weight		730 X 660 X 1200 (mm) / 110kg						
Controller Type		Capactive button						
Per Serving		50 servings (total : 150 servings)	Memorizable Recipes		-			
Steps per Recipe		4 steps	Container		Ø450 X 165mm (26L)			
General Output								
Warming		H1 ~ H7 (7 Steps)	Heating			1 ~ 10 (10 steps)		
Output per Warming Steps		H1	H2	H3	H4	H5	H6	H7
		40Wh	60Wh	100Wh	130Wh	170Wh	240Wh	350Wh
Functions & Features		Error Code						
		- No vessel : Error "00"						
		- Over current indication : Error "E1"						
		- Over voltage indication : Error "E2" (Above 265V)						
		- Low voltage : Error "E3" (Below 180V)						
		- Product over heated indication : Error "E4" (IGBT heat sink above 85°C)						
		- Unstable power indication: Error "E7"						
- Defective PCB indication : Error "E8"								
- Defective Working Coil indication : Error "E9"								
Functions & Features		General Cooking System						
		- Even if you use cold water for rice(10°C blow), the machine keeps rice warm(15~20°C)						
		- Rice cooker works at user's setting temperature. (First Setting 150°C)						
		- Cooking process shows on the LED. (Ready->Cooking->Stand by->Done)						
Functions & Features		Timer Setting						
		- Between 0sec - 60min (1hr)						
Warranty		1 year (to be charged in case of user's negligence)						

Installation Guide

Electric Wiring



- ▶ Electricity : 380V 3PH+N
- ▶ Circuit breaker : 20A or above
- ▶ Cables : 600V, 6SQMM or above, 4phase
- ▶ Ground cable separated : 600/1000V, 4SQMM or above

Seoul Office: #75, Achasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.